



TECHNICAL DATA SHEET

NITRILE EXAMINATION GLOVES

Product Code: GLP0065(Powder free) GLP0055(Powdered)

Sizes Available: Small, Medium, Large and Extra Large

Packing: 100 pieces per box
10 boxes per case

Dimensions

Length: Not less than 240 mm

Width:	Extra Small	75 +/- 5 mm
	Small	85 +/- 5 mm
	Medium	95 +/- 5 mm
	Large	106 +/- 5 mm
	Extra Large	116 +/- 5mm

Thickness (single wall): Not less than 0.08 mm

Specifications

Puncture Resistance: Not less than 5.0 N

Average Weight: 5.84 g
Calculated Glove Surface Area/ cm² = 1,130

Unaged
Tensile Strength (MPA): Not less than 14.0

Elongation, %: Not less than 500

Force at Break: Not less than 7.5 N

Aged 70 +/- 2°C for 7 Days
Tensile Strength (MPA): Not less than 7.5

Elongation, %: Not less than 500

Force at Break: Not less than 5.5 N

<u>Electrostatic Properties</u>	<u>Static Decay</u>	<u>Surface Resistivity (ohms/sq)</u>
50% Humidity	<2 Seconds	1 x10 (10) ohms/square
Relative Humidity	< 5 Seconds	1 x10 (12) ohms/square

a division of ...



www.tsmfg.com

Voice: 888-460-4440 / 760-598-5599
Fax: 888-966-5550 / 760-598-2145
1445 Engineer St
Vista, CA 92081 USA